

## Performance parameter table

number	model	caliber (mm)	flow (m <sup>3</sup> /h)	lift (m)	Rotating speed (r/min)	power (kW)	efficiency (%)	weight (kg)	Water pump electrical control	auto coupler	Lift applicatio n range
1	25WQ8-22-1.1	25	8	22	2825	1.1	38.1	42	QZD-1.1	GAK-25	10-22
2	32WQ12-15-1.1	32	12	15	2825	1.1	40	42	QZD-1.1	GAK-32	8-15
3	40WQ15-15-1.5	40	15	15	2840	1.5	45.1	52	QZD-1.5	GAK-50	6-15
4	40WQ15-30-2.2	40	15	30	2840	2.2	48	55	QZD-2.2	GAK-50	15-30
5	50WQ20-7-0.75	50	20	7	1390	0.75	54	50	QZD-0.75	GAK-50	3-7
6	50WQ10-10-0.75	50	10	10	1390	0.75	56	50	QZD-0.75	GAK-50	4-10
7	50WQ20-15-1.5	50	20	15	2840	1.5	55	55	QZD-1.5	GAK-50	6-15
8	50WQ15-25-2.2	50	15	25	2840	2.2	56	60	QZD-2.2	GAK-50	10-25
9	50WQ18-30-3	50	18	30	2880	3	58	70	QZD-3	GAK-50	15-30
10	50WQ25-32-5.5	50	25	32	2900	5.5	53	100	QZD-5.5	GAK-50	17-32
11	50WQ20-40-7.5	50	20	40	2900	7.5	55	110	QZD-7.5	GAK-50	20-40
12	65WQ25-15-2.2	65	25	15	2840	2.2	52	60	QZD-2.2	GAK-65	6-15
13	65WQ37-13-3	65	37	13	2880	3	55	70	QZD-3	GAK-65	6-13
14	65WQ25-30-4	65	25	30	2890	4	58	85	QZD-4	GAK-65	15-30
15	65WQ30-40-7.5	65	30	40	2900	7.5	56	110	QZD-7.5	GAK-65	20-40
16	65WQ35-50-11	65	35	50	2930	11	60	200	JJ1-11	GAK-65	35-50
17	65WQ35-60-15	65	35	60	2930	15	63	230	JJ1-15	GAK-65	40-60
18	80WQ40-7-2.2	80	40	7	1420	2.2	52	75	QZD-2.2	GAK-80	3-7
19	80WQ43-13-3	80	43	13	2880	3	50	85	QZD-3	GAK-80	5-13
20	80WQ40-15-4	80	40	15	2890	4	57	90	QZD-4	GAK-80	6-15
21	80WQ65-25-7.5	80	65	25	2900	7.5	56	135	QZD-7.5	GAK-80	12-25
22	100WQ80-10-4	100	80	10	1440	4	62	130	QZD-4	GAK-100	4-10
23	100WQ110-10-5.5	100	110	10	1440	5.5	66	155	QZD-5.5	GAK-100	5-10
24	100WQ100-15-7.5	100	100	15	1440	7.5	67	170	QZD-7.5	GAK-100	8-15
25	100WQ85-20-7.5	100	85	20	1440	7.5	68	170	QZD-7.5	GAK-100	10-20
26	100WQ100-25-11	100	100	25	1460	11	65	270	JJ1-11	GAK-100	10-25
27	100WQ100-30-15	100	100	30	1460	15	66	300	JJ1-15	GAK-100	12-30
28	100WQ100-35-18.5	100	100	35	1470	18.5	65	380	JJ1-18.5	GAK-100	15-35
29	125WQ130-15-11	125	130	15	1460	11	62	380	JJ1-11	GAK-125	7-15
30	125WQ130-20-15	125	130	20	1460	15	63	300	JJ1-15	GAK-125	10-20
31	150WQ145-9-7.5	150	145	9	1440	7.5	63	180	QZD-7.5	GAK-150	4-9
32	150WQ180-15-15	150	180	15	1470	15	65	280	JJ1-15	GAK-150	5-15
33	150WQ180-20-18.5	150	180	20	1470	18.5	75	400	JJ1-18.5	GAK-150	8-20
34	150WQ180-25-22	150	180	25	1470	22	76	430	JJ1-22	GAK-150	12-25
35	150WQ130-30-22	150	180	30	1470	22	75	450	JJ1-22	GAK-150	15-30
36	150WQ180-30-30	150	180	30	1470	30	73	500	JJ1-30	GAK-150	15-30
37	150WQ200-30-37	150	200	30	1480	37	70	600	JJ1-37	GAK-150	15-30
38	150WQ160-45-37	150	160	45	1450	37	65	650	JJ1-37	GAK-150	20-45
39	200WQ300-7-11	200	300	7	970	11	73	450	JJ1-11	GAK-200	15-30
40	200WQ250-11-15	200	250	11	970	15	74	400	JJ1-15	GAK-200	4-11

## Performance parameter table

number	model	caliber (mm)	flow (m <sup>3</sup> /h)	lift (m)	Rotating speed (r/min)	power (kW)	efficiency (%)	weight (kg)	Water pump electrical control	auto coupler	Lift applicatio n range
41	200WQ400-10-22	200	400	10	1470	22	76	450	JJ1-22	GAK-200	5-10
42	200WQ400-13-30	200	400	13	1470	30	73	650	JJ1-30	GAK-200	6-13
43	200WQ250-15-18.5	200	250	15	1470	18.5	72	500	JJ1-18.5	GAK-200	7-15
44	200WQ300-15-22	200	350	15	1470	22	73	550	JJ1-22	GAK-200	8-15
45	200WQ250-22-30	200	250	22	1470	30	71	800	JJ1-30	GAK-200	12-22
46	200WQ350-25-37	200	350	25	1480	37	75	850	JJ1-37	GAK-200	10-25
47	200WQ380-28-45	200	380	28	1450	45	70	920	JJ1-45	GAK-200	13-28
48	200WQ400-30-55	200	400	30	1480	55	70	1000	JJ1-55	GAK-200	13-30
49	200WQ350-40-75	200	350	40	1450	75	68	1000	JJ1-75	GAK-200	20-40
50	250WQ600-9-30	250	600	9	980	30	74	850	JJ1-30	GAK-250	3-9
51	250WQ600-12-37	250	600	12	1480	37	78	850	JJ1-37	GAK-250	5-12
52	250WQ600-15-45	250	600	15	1480	45	75	950	JJ1-45	GAK-250	6-15
53	250WQ600-20-55	250	600	20	1480	55	73	1300	JJ1-55	GAK-250	8-20
54	250WQ600-25-75	250	600	25	1480	75	73	1500	JJ1-75	GAK-250	12-25
55	300WQ800-12-45	300	800	12	1480	45	76	1500	JJ1-45	GAK-300	5-12
56	300WQ500-15-45	300	500	15	980	45	70	1500	JJ1-45	GAK-300	7-15
57	300WQ800-15-55	300	800	15	980	55	73	1550	JJ1-55	GAK-300	8-15
58	300WQ600-20-55	300	600	20	980	55	75	1550	JJ1-55	GAK-300	10-20
59	300WQ800-20-75	300	800	20	980	75	78	1600	JJ1-75	GAK-300	12-20
60	300WQ950-20-90	300	950	20	980	90	80	1700	JJ1-90	GAK-300	11-20
61	300WQ1000-25-110	300	1000	25	980	110	82	2000	JJ1-110	GAK-300	12-25
62	300WQ800-32-110	300	800	32	1450	110	76	2000	JJ1-110	GAK-300	16-32
63	350WQ1100-10-55	350	1100	10	980	55	84.5	1380	JJ1-55	GAK-350	4-10
64	350WQ1500-15-90	350	1500	15	980	90	82.5	2000	JJ1-90	GAK-350	6-15
65	350WQ1200-18-90	350	1200	18	980	90	83.1	2000	JJ1-90	GAK-350	8-18
66	350WQ1100-28-132	350	1100	28	740	132	83.2	2520	JJ1-132	GAK-350	15-25
67	350WQ1000-36-160	350	1000	36	740	160	78.5	2880	JJ1-160	GAK-350	20-36
68	400WQ1500-10-75	400	1500	10	980	75	82.1	1750	JJ1-75	GAK-400	3-10
69	400WQ2200-9-110	400	2200	9	980	110	80	2100	JJ1-110	GAK-400	3-9
70	400WQ2000-15-132	400	2000	15	740	132	85.5	2520	JJ1-132	GAK-400	6-15
71	400WQ1700-22-160	400	1700	22	740	160	82.1	2880	JJ1-160	GAK-400	10-22
72	400WQ1500-26-160	400	1500	26	740	160	83.5	2880	JJ1-160	GAK-400	12-36
73	400WQ1700-30-200	400	1700	30	740	200	83.5	3850	JJ1-200	GAK-400	15-30
74	400WQ1800-32-250	400	1800	32	740	250	82.1	4690	JJ1-200	GAK-400	17-32
75	400WQ1760-7.5-55	400	1760	7.5	580	55	82.3	2000	JJ1-55	GAK-400	4-7.5
76	500WQ2500-10-110	500	2500	10	740	110	82	2100	JJ1-110	GAK-500	2-10
77	500WQ2600-15-160	500	2600	15	740	160	83	2280	JJ1-160	GAK-500	4-15
78	500WQ3000-15-200	500	3000	15	740	200	82	2250	JJ1-200	GAK-500	8-15
79	500WQ2400-22-220	500	2400	22	740	220	84	2350	JJ1-220	GAK-500	8-22
80	500WQ4000-15-250	500	4000	15	980	250	84	2650	JJ1-250	GAK-500	8-15
81	500WQ2600-24-250	500	2600	24	740	250	82	2650	JJ1-250	GAK-500	10-24