



## ELECTRONIC SPECIFICATIONS:

PART NO	Primary [V]	Secondary [V]	Current [mA]	Ambient TEMP.(°C)	Weight (g)	Certificate			
						VDE	UL	CQC	CE
XP601-848	115V 50/60Hz	4.5V	7777mA	T40 B	783		•		•
XP601-849	115V 50/60Hz	6V	5833mA	T40 B	783		•		•
XP601-850	115V 50/60Hz	7.5V	4666mA	T40 B	783		•		•
XP601-851	115V 50/60Hz	9V	3888mA	T40 B	783		•		•
XP601-852	115V 50/60Hz	12V	2916mA	T40 B	783		•		•
XP601-853	115V 50/60Hz	15V	2333mA	T40 B	783		•		•
XP601-854	115V 50/60Hz	18V	1944mA	T40 B	783		•		•
XP601-855	115V 50/60Hz	24V	1458mA	T40 B	783		•		•
XP602-856	115V 50/60Hz	2x4.5V	2x3888mA	T40 B	783		•		•
XP602-857	115V 50/60Hz	2x6V	2x2916mA	T40 B	783		•		•
XP602-858	115V 50/60Hz	2x7.5V	2x2333mA	T40 B	783		•		•
XP602-859	115V 50/60Hz	2x9V	2x1944mA	T40 B	783		•		•
XP602-860	115V 50/60Hz	2x12V	2x1458mA	T40 B	783		•		•
XP602-861	115V 50/60Hz	2x15V	2x1166mA	T40 B	783		•		•
XP602-862	115V 50/60Hz	2x18V	2x972mA	T40 B	783		•		•
XP602-863	115V 50/60Hz	2x24V	2x729mA	T40 B	783		•		•
XP601-948	230V 50/60Hz	4.5V	7777mA	T40 B	783		•	•	•
XP601-949	230V 50/60Hz	6V	5833mA	T40 B	783		•	•	•
XP601-950	230V 50/60Hz	7.5V	4666mA	T40 B	783		•	•	•
XP601-951	230V 50/60Hz	9V	3888mA	T40 B	783		•	•	•
XP601-952	230V 50/60Hz	12V	2916mA	T40 B	783		•	•	•
XP601-953	230V 50/60Hz	15V	2333mA	T40 B	783		•	•	•
XP601-954	230V 50/60Hz	18V	1944mA	T40 B	783		•	•	•
XP601-955	230V 50/60Hz	24V	1458mA	T40 B	783		•	•	•
XP602-956	230V 50/60Hz	2x4.5V	2x3888mA	T40 B	783		•	•	•
XP602-957	230V 50/60Hz	2x6V	2x2916mA	T40 B	783		•	•	•
XP602-958	230V 50/60Hz	2x7.5V	2x2333mA	T40 B	783		•	•	•
XP602-959	230V 50/60Hz	2x9V	2x1944mA	T40 B	783		•	•	•
XP602-960	230V 50/60Hz	2x12V	2x1458mA	T40 B	783		•	•	•
XP602-961	230V 50/60Hz	2x15V	2x1166mA	T40 B	783		•	•	•
XP602-962	230V 50/60Hz	2x18V	2x972mA	T40 B	783		•	•	•
XP602-963	230V 50/60Hz	2x24V	2x729mA	T40 B	783		•	•	•